PACEMAKER 1st Demo

곽신우 (201411260)

문성찬 (201511260)

배율희 (201511266)


주재빈 (201511298)





CONTENTS

- I. WHAT IS PACEMAKER
- II. QUESTION GENERATION
- III. SERVER AND DATABASE
- IV. USER INTERFACE
- V. SAMPLE



WHAT IS PACEMAKER

Your Running Mate

When you run,

We are with you.

When you are tired,

We are waiting for you.


On the way you want to go, We are with you.

We cheer the way you go.



WHAT IS PACEMAKER

Domain Model



WHAT IS PACEMAKER


«Python Server» Django

Blueprint

Docker

Docker Contaner

MySQL



PACEMAKER

AWS S3 Server

What is Question Generation?

Paragraph

Since mid-May, Uber has required drivers to take selfies to verify they are wearing **a mask** or face covering before they are able to pick up riders.

Soon, certain riders will also be required to take a selfie prior to ordering a ride.

Question

What is required to be checked before Uber's drivers must take selfies?


Answer: a mask

Question

Who will be required to take a selfie before ordering a ride?

Answer: certain riders

Question Generation using Language Model



자연어를 이해하며 자연어를 생성할 수 있는 언어모델

- 자연어 단락과 정답 스판을 주입
- 정답과 연관되는 질문을 생성시킨다


정답 스판 선택의 자동화

a mask


- 단어의 중요도를 평가하는 TF-IDF 메트릭 활용

Microsoft Unified Language Model

- 하나의 트랜스포머에 각기 다른 언어 모델에 특화된 태스크들을 학습시켰다.
- 그래서 자연어 이해와 생성이 모두 가능한 일반화된 언어모델을 목표함




문장 맥락을 이전에 등장한 단어와의 연관으로 이해



Bidirectional LM


문장 맥락을 모든 단어와의 연관으로 이해



Segence to Sequence LM

주어진 맥락에 적절한 문장을 생성하는 법을 이해

UniLM-v1 Architecture



TF-IDF Metric

TF-IDF = (문서 내 단어 빈도) * log(전체 문서 수)/ (단어가 나타나는 문서 수))

- 한 문서에 빈번히 등장하는 단어는 중요할 것이다
- 여러 문서에 계속해서 등장하는 단어는 덜 중요할 것이다


QG 모델의 입력 = (단락, 정답 스판)

- 정답 스판 선택을 자동화하기 위해 명사들의 TF-IDF 값 정렬 후 선택

Since mid-May, Uber has required drivers to take selfies to verify they are wearing a mask or face covering before they are able to pick up riders.

Soon, certain riders will also be required to take a **selfie** prior to ordering a **ride**.


App Server Runtime Environment



Data Base Runtime Environment




Server-DB Communication




- 기본적으로 Django에서 지원하는 ORM 통신을 사용한다.
- Docker 사용에 의해 보안성이, Django에서 지원하는 ORM에 의해 속도가 다소 확보되었기에 Query가 복잡해지는 경우에는 ORM이 아닌 Query를 작성하여 직접 통신하는 방법 역시 고려한다.


App Server Model



Data Base Model



Data Base Model




USER INTERFACE UI Concept

목표를 완주하기까지 교사와 학생의 옆에서 '페이스메이커'로서 함께 달린다는 컨셉을 바탕으로 한다.


러닝트랙을 형상화한 직선과 곡선으로 기본 레이아웃과 아이콘을 구성하고, 고 해상도 사진으로 강조를 주는 디자인.






USER INTERFACE


UI Structure



SAMPLE Select Channel and Leader Channel




SAMPLE Make BKD and Request QG



SAMPLE

Make Reservation and Receive



SAMPLE UniLM-v1 Sample

paragraph

Since mid-May, Uber has required drivers to take selfies to verify they are wearing a mask or face covering before they are able to pick up riders.

paragraph

Soon, certain riders will also be required to take a selfie prior to ordering a ride.

result

Q: Who has Uber required to take selfies?

A: drivers

result

Q: What kind of face covering does Uber require drivers to wear before they can pick?

A:a mask

result

Q: Who will be required to take a selfie prior to ordering a ride?

A: certain riders

result

Q: Who will be required to take a selfie before ordering what?

A: a ride